

Christie MicroTiles LED

Indoor LED tiles



Technical specification		1.0mm (Series 80)	0.75mm (Series 60)
Display technology	pixel pitch	• 1.0mm	• 0.75mm
	pixel configuration	• 3 LED diodes in 1 package (1R1G1B)	• 4 pixels in 1 package (4R4G4B)
	maximum calibrated brightness	• 2000 nits (cd/m ²) calibrated	
	aspect ratio	• 8:9	
	contrast ratio (full field)	• Greater than 10000:1	• Greater than 8000:1
	viewing angle	• 160° H, 140° V	
	refresh rate	• Up to 3840 Hz	
	scan rate	• 1/15	• 1/60
	color temperature	• 2700-9600K	
	display colors	• 18014 trillion (18-bit)	
color space	• P3		
LED lifespan (50% brightness)	• 100,000 hours		
runtime	• 24/7		
Signal	inputs	• 2 x HDMI 2.0 (HDCP), 2 x DisplayPort 1.2 (HDCP)	
	outputs	• 2 x QSFP+ (Bi-directional)	
	control	• 1 x RJ45 Ethernet, USB (RS232 via dongle)	
Power	power input rating	• 100-240 VAC @ 50/60 Hz - remote power supply ¹ • 48-56 VDC • 48V Power over Ethernet - per tile	
	power consumption per tile	• 23 W typical, 46 W maximum	• 15 W typical, 50 W maximum
	heat output per tile	• 78 BTU/hr typical; 156 BTU/hr maximum	• 51 BTU/hr typical; 105 BTU/hr maximum
Environment	operating temperature	• 32-104F (0-40C)	
	operating humidity	• 10-90% RH non-condensing	
	storage temperature	• 14-122F (-10-50C)	
	environment	• Indoor	
	IP rating	• 30	
Physical	tile dimensions (installed)	• (W x H x D) 9.45 x 10.63 x 3.35" (240 x 270 x 85mm)	
	tile diagonal	• 14.22" (361mm)	
	tile area	• 0.70ft ² (0.0648m ²)	
	tile resolution	• 240 x 270	• 320 x 360
	tile weight	• 4.85lbs (2.2kg) per tile • 74.85lbs (34.0kg) per square meter • Total installed weight (including proprietary QuickMount™ system) • 7.06lbs (3.2kg) per tile, 108.95lbs (49.4kg) per square meter	
	tile design	• Die-cast aluminum	
	service access	• All service from front	
	installation options	• Flat • Concave • Convex • 90 degree outside and inside corner • Hanging/flying • Creative shapes	
	direct mount system	• QuickMount system included - mounting plates, mounting template, wall anchors	
	additional required components	• Remote power supply rack shelf • Power supply unit modules (rectifiers) • Tile controller (Octroller), and wall controller sold separately	
Certifications ²	• UL60950, FCC, CE, EMC, RoHS, RC2		
Warranty	• Three years parts and labor limited warranty, extended warranty option available for a one-time fee at time of purchase		

¹ See remote power specifications for full details.

² Certain of the listed certifications may be pending and not yet issued. For the current status of the listed certifications, please contact an authorized Christie representative.


Performance specifications are typical. Due to constant research, specifications are subject to change without notice.

Octroller

Signal	
inputs	• 2 x QSFP+ (Bi-directional)
outputs	• 8 X RJ45 Ethernet (PoE up to 75W per port)
control	• 1 x RJ45 Ethernet
Power	
power input rating	• 48-56 VDC
power consumption	• 600W maximum
Environment	
operating temperature	• 32-104F (0-40C)
operating humidity	• 10-90% RH non-condensing
storage temperature	• 14-122F (-10-50C)
environment	• Indoor

QuickMount system

Proprietary QuickMount system includes custom mounting templates, laser-cut steel mounting sheets and machined wall anchors to eliminate any alignment challenges, reducing time and cost.



For the most current specification information, please visit christiedigital.com

Copyright 2023 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified.

All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.

CD3540-MicroTilesLED-0.75-1mm-Datasheet-Jun-23-EN

CHRISTIE®