

CHRISTIE JAZZ SERIES

DWU1800-JS / DWU2400-JS / 4K1600-JS / 4K2100-JS

Corporate | Hospitality & tourism | Museums | Worship | Rental & staging | Theme parks & attractions

Outstandingly bright with up to 23,750 lumens, impressively light with a chassis that weighs less than 65 lbs (30 kg), and incredibly priced.



Five-year warranty for extra peace of mind.

Complete solutions that work for you

Jazz Series seamlessly integrates into a complete Christie® solution with features like onboard Twist™ warping and blending, optional Mystique™ automated camera-based alignment, and compatibility with Christie Intelligent Camera.

Reliability you can trust

Get extra peace of mind with our industry-leading five-year warranty and virtually maintenance-free operation that works for you 24/7.

Key features

- › **Dynamic contrast for lifelike imagery:** Dive into a world of depth and detail with a dynamic contrast ratio of 25,000:1.
- › **Cutting edge, advanced electronics:** Texas Instruments' 0.8" HEP DMD and optical design give you improved color, contrast, and a more efficient cooling system design.
- › **Wide range of lens options:** With nine interchangeable lenses, including two ultra-short throw lenses, you can find the lens that works best for your project.
- › **Reliable laser light source:** 20,000 hours in Standard mode and 50,000 hours in ECO1 mode.



CHRISTIE®

Technical specifications

DWU1800-JS / DWU1800A-JS (TAA)

DWU2400-JS / DWU2400A-JS (TAA)

Image	brightness ¹	<ul style="list-style-type: none"> • 17,800 ISO lumens • 15,000 ANSI lumens 	<ul style="list-style-type: none"> • 23,750 ISO lumens • 20,000 ANSI lumens
	color wheel	• 4 segment - 3X speed	
	contrast (nominal)	<ul style="list-style-type: none"> • Christie RealBlack™ enabled: 4,000,000:1 • RealBlack disabled: 1,500: 1 (Native) • Dynamic contrast: 25,000:1 (Center) 	
Display technology	type	• 1 x 0.8" HEP DMD	
	resolution	• WUXGA 1920 x 1200 (2,304,000 pixels) (16:10)	
Illumination	type	• High-efficiency blue laser phosphor	
	performance	<ul style="list-style-type: none"> • 20,000 hours to 50% brightness at full power mode • 50,000 hours to 50% brightness at ECO1 mode 	
Signal Inputs	standard	<ul style="list-style-type: none"> • HDMI 2.0b x 2 (HDCP 1.4/2.2) • 3G-SDI x 1 (BNC) • DisplayPort x 1(1.2a) • USB 2.0 x 1 (Type A) • HDBaseT 1.0 (RJ45) x 1 	
	signals	• Horizontal and vertical scaling while maintaining aspect ratio (all inputs)	
	2D	<ul style="list-style-type: none"> • HDMI and DisplayPort: 3840 x 2160 up to 60 Hz, 1920 x 1080 between 24-240 Hz • Display Port: 3840 x 2400 up to 60 Hz, 1920 x 1200 between 24-120 Hz • 3G HDS DI: 1920 x 1080 up to 60 Hz 	
	3D	<ul style="list-style-type: none"> • Active shuttered and passive polarized stereoscopic 3D • Blu-Ray: frame packing, top/bottom, side-by-side at 720p, 1080p at 24-60 Hz frame sequential up to 120 Hz (up to 60 Hz per eye) • Active 3D input (HDMI and DP): 1920 x 1080 up to 120 Hz (up to 60 Hz per eye), 3840 x 2160 at 60 Hz (30 Hz per eye) • Active 3D input (DP only): 1920 x 1200 up to 120 Hz (up to 60 Hz per eye), 3840 x 2400 at 60Hz (30 Hz per eye) • Dual input 3D (2x HDMI): 1920 x 1080 up to 120 Hz (up to 60 Hz per eye), 3840 x 2160 at 60 Hz (60 Hz per eye) • 3D sync in (BNC) • 3D sync out (BNC) to emitter or active polarizer 	
	pixel clock	• 600 MHz	
	scan rates	• Horizontal: 15.375 kHz ~ 135.0 kHz ; Vertical: 23.98 Hz ~ 120 Hz	
Signal Outputs	monitor out (loop-through)	• 3G-SDI x 1 (BNC) • HDMI x 1 (HDMI out)	
Control and networking		<ul style="list-style-type: none"> • HDBaseT (RJ45 x 1) • RJ45 x 1 (Ethernet control over wired network connection) • RS232 x 1 • Remote in: 3.5 mm stereo female (provides serial communications and power) • DC jack 12 VDC, 200 mA max 	
	standard	• Christie Twist™	
	optional	<ul style="list-style-type: none"> • Twist Premium and Twist Pro • Mystique™ automated camera-based alignment 	
	TAA-compliant	• Yes	
Lenses	mount type	<ul style="list-style-type: none"> • Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses) 	
	lens options	• 0.34-0.37:1 ultra short throw lens • 0.46:1 ultra short throw lens	
	zoom/focus memory	<ul style="list-style-type: none"> • 0.78-0.9:1 zoom lens • 0.9-1.3:1 zoom lens • 1.3-1.8:1 zoom lens • 1.8-2.4:1 zoom lens • 2.4-4.8:1 zoom lens • 4.8-8.64:1 zoom lens • 8.64-12.96 zoom lens 	
Accessories	standard	• IR remote with wired remote jack (wire not included) • AC line cord for projector • Product Safety Guide	
	optional	<ul style="list-style-type: none"> • Christie® One Mount Plus (140-117100-XX) • One Mount Extender Rod (121-125109-XX) • Christie One Rigging Frame V2 (140-155102-XX) 	<ul style="list-style-type: none"> • Christie Intelligent Camera (156-155102-XX) • One Mount Rigging Kit (used with One Mount, One Mount Plus Extender Rod) (121-126100-XX)
Power requirements	operating voltage	• Normal: 100-240 VAC at 50/60 Hz	<ul style="list-style-type: none"> • Normal: 100-240 VAC at 50/60 Hz • Supports 100-20 VAC at reduced power with 80% brightness level output
	power consumption (25 C, 220 V)	• Normal: 930W • ECO1: 760W • ECO2: 530W	• Normal: 1,290W • ECO1: 990W • ECO2: 670W
	operating current	<ul style="list-style-type: none"> • Normal: 4.23 A (220-240 VAC) • 8.73 A (100-120 VAC) 	<ul style="list-style-type: none"> • Normal: 5.86 A (220-240 VAC) • 9.27 A (100-120 VAC)
	dissipation at 220 V	<ul style="list-style-type: none"> • Normal: 3,173 BTU/hr • ECO1: 2,593 BTU/hr • ECO2: 1,808 BTU/hr 	<ul style="list-style-type: none"> • Normal: 4,401 BTU/hr • ECO1: 3,378 BTU/hr • ECO2: 2,286 BTU/hr
Audible noise		• Standard: 44dBA (max) • ECO2: 40dBA (max)	• Standard: 47dBA (max) • ECO2:42dBA (max)
Standby power	LAN off	• < 0.3W	
	LAN on	• < 6W	
Physical	size	• (LxWxH) 23.6 x 20.5 x 7.6" (600 x 520 x 193 mm) without feet	
	shipping size	• (LxWxH) 38 x 31.30 x 14.6" (965 x 795 x 370 mm)	
	weight	• 64.76 lbs (29.4 kg)	
	shipping weight	• 94.71 lbs (43.0 kg)	
Operating environment	temperature	• 32-113 F (0-45 C) (0-2,500 ft. altitude)	
	humidity	• 10-85% non-condensing	
Regulatory		<ul style="list-style-type: none"> • This product conforms to all relevant European directives, standards, safety, health, and environmental concerns • Directives: RoHS • REACH • WEEE • Contact Christie for timing of certifications: UL/CSA/IEC 60950-1 • FCC Class A • cTUVus • CE • FDA • CCC • KC • PSE • BIS • VCCI • RCM • Mexico • BSMI 	
Warranty		<ul style="list-style-type: none"> • Five years parts and labor on the projector • Five years or 20,000 hours parts and labor on the illumination system • Contact an authorized Christie representative for full details of our limited warranty 	
Special Features		<ul style="list-style-type: none"> • 21:9 aspect ratio support and customize EDID • Fade in & fade out control for shutter function • Supports 4K 3840 x 2160 and 4096 x 2160 signal inputs • Supports control systems: Crestron Roomview V2 • PLink V2 • AMX - Device Discovery 	

¹ Brightness level is +/- 5%

Technical specifications

4K1600-JS / 4K1600A-JS (TAA)

4K2100-JS / 4K2100A-JS (TAA)

Image	brightness ¹	<ul style="list-style-type: none"> • 16,600 ISO lumens • 14,000 ANSI lumens 	<ul style="list-style-type: none"> • 21,350 ISO lumens • 18,000 ANSI lumens 	
	color wheel	• 4 segment - 4X speed		
	contrast (nominal)	<ul style="list-style-type: none"> • Christie RealBlack™ enabled: 4,000,000:1 • Christie® RealBlack disabled: 1,500: 1 (Native) • Dynamic contrast: 25,000:1 (Center) 		
Display technology	type	• 1 x 0.8" HEP DMD		
	resolution	• 4K UHD+ 3840 x 2400 (9,216,000 pixels) (16:10)		
Illumination	type	• High-efficiency blue laser phosphor		
	performance	<ul style="list-style-type: none"> • 20,000 hours to 50% brightness at full power mode • 50,000 hours to 50% brightness at ECO1 mode 		
Signal Inputs	standard	<ul style="list-style-type: none"> • HDMI 2.0b x 2 (HDCP 1.4/2.2) • 12G-SDI x 1 (BNC) • DisplayPort x 1(1.2a) • USB 2.0 x 1 (Type A) • HDBaseT 3.0 (RJ45) x 1 		
	signals	• Horizontal and vertical scaling while maintaining aspect ratio (all inputs)		
	2D	<ul style="list-style-type: none"> • HDMI and DisplayPort: 3840 x 2160 up to 60 Hz, 1920 x 1080 between 24-240 Hz • Display Port: 3840 x 2400 up to 60 Hz, 1920 x 1200 between 24-120 Hz • 12G HDS DI: 3840 x 2160 up to 60 Hz, 1920 x 1080 up to 60 Hz 		
	3D	<ul style="list-style-type: none"> • Active shuttered and passive polarized stereoscopic 3D • Blu-Ray: frame packing, top/bottom, side-by-side at 720p, 1080p at 24-60 Hz frame sequential up to 120 Hz (up to 60 Hz per eye) • Active 3D input (HDMI and DP): 1920 x 1080 up to 120 Hz (up to 60 Hz per eye), 3840 x 2160 at 60 Hz (30 Hz per eye) • Active 3D input (DP only): 1920 x 1200 up to 120 Hz (up to 60 Hz per eye), 3840 x 2400 at 60 Hz (30 Hz per eye) • Dual input 3D (2x HDMI): 1920 x 1080 up to 120 Hz (up to 60 Hz per eye), 3840 x 2160 at 60 Hz (60 Hz per eye) • 3D sync in (BNC) • 3D sync out (BNC) to emitter or active polarizer 		
	pixel clock	• 600 MHz		
	scan rates	• Horizontal: 15.375 kHz ~ 135.0 kHz ; Vertical: 23.98 Hz ~ 120 Hz		
Signal Outputs	monitor out (loop-through)	• 12G-SDI x 1 (BNC) • HDMI x 1 (HDMI out)		
Control and networking		<ul style="list-style-type: none"> • HDBaseT 3.0 (RJ45 x 1) • RJ45 x 1 (Ethernet control over wired network connection) • RS232 x 1 • Remote in: 3.5 mm stereo female (provides serial communications and power) • DC jack 12 VDC, 200 mA (max) 		
	Warping and blending	mount type	• Christie Twist™	
		optional	<ul style="list-style-type: none"> • Twist Premium and Twist Pro • Mystique™ automated camera-based alignment 	
	TAA-compliant		• Yes	
Lenses	mount type	<ul style="list-style-type: none"> • Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses) 		
	lens options	• 0.34-0.37:1 ultra short throw lens • 0.46:1 ultra short throw lens		
	zoom/focus memory	<ul style="list-style-type: none"> • 0.78-0.9:1 zoom lens • 0.9-1.3:1 zoom lens • 1.3-1.8:1 zoom lens • 1.8-2.4:1 zoom lens • 2.4-4.8:1 zoom lens • 4.8-8.64:1 zoom lens • 8.64-12.96 zoom lens 		
Accessories	standard	• IR remote with wired remote jack (wire not included) • AC line cord for projector • Product Safety Guide		
	optional	<ul style="list-style-type: none"> • Christie® Intelligent Camera (156-155102-XX) • One Mount Rigging Kit (used with One Mount, One Mount Plus Extender Rod) (121-126100-XX) 	<ul style="list-style-type: none"> • Christie Intelligent Camera (156-155102-XX) • One Mount Rigging Kit (used with One Mount, One Mount Plus Extender Rod) (121-126100-XX) 	
Power requirements	operating voltage	• Normal: 100-240 VAC at 50/60 Hz	<ul style="list-style-type: none"> • Normal: 100-240 VAC at 50/60 Hz • Supports 100-120 VAC at reduced power with 80% brightness level output. 	
	power consumption (25 C, 220 V)	• Normal: 1,020W • ECO1: 840W • ECO2: 580W	• Normal: 1,340W • ECO1: 1,080W • ECO2: 710W	
	operating current	<ul style="list-style-type: none"> • Normal: 4.64 A (220-240 VAC) • 9.55 A (100-120 VAC) 	<ul style="list-style-type: none"> • Normal: 6.09 A (220-240 VAC) • 10.09 A (100-120 VAC) 	
	dissipation at 220 V	<ul style="list-style-type: none"> • Normal: 3,480 BTU/hr • ECO1: 2,866 BTU/hr • ECO2: 1,979 BTU/hr 	<ul style="list-style-type: none"> • Normal: 4,572 BTU/hr • ECO1: 3,685 BTU/hr • ECO2: 2,423 BTU/hr 	
Audible noise		• Standard: 45dBA (max) • ECO2: 43dBA (max)	• Standard: 49dBA (max) • ECO2: 45dBA (max)	
Standby power	LAN off	• < 0.3W		
	LAN on	• < 6W		
Physical	size	• (LxWxH) 23.6 x 20.5 x 7.6" (600 x 520 x 193 mm) without feet		
	shipping size	• (LxWxH) 38 x 31.30 x 14.6" (965 x 795 x 370 mm)		
	weight	• 64.76 lbs (29.4 kg)		
	shipping weight	• 94.71 lbs (43.0 kg)		
Operating environment	temperature	• 32-113 F (0-45 C) (0-2,500 ft. altitude)		
	humidity	• 10-85% non-condensing		
Regulatory		<ul style="list-style-type: none"> • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives: RoHS • REACH • WEEE • Contact Christie for timing of certifications: UL/CSA/IEC 60950-1 • FCC Class A • cTUVus • CE • FDA • CCC • KC • PSE • BIS • VCCI • RCM • Mexico • BSMI 		
Warranty		<ul style="list-style-type: none"> • Five years parts and labor on the projector • Five years or 20,000 hours parts and labor on the illumination system • Contact an authorized Christie representative for full details of our limited warranty 		
Special Features		<ul style="list-style-type: none"> • 21:9 aspect ratio support and customize EDID. • Fade in & fade out control for shutter function • High Frame Rate 1080P at 240 Hz • Support Control System: Crestron Roomview V2 • PLink V2 • AMX - Device Discovery 		

¹ Brightness level is +/- 5%

For the most current specification information, please visit christiedigital.com/Jazz

Copyright 2026 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
CD73902-Jazz-Datasheet-Updates-Jan-26-EN

